



NOTCH LEGS OVER HEAD SEAM

| NO. QTY | DESCRIPTION | SPEC | SUB-DWG. |
|---------|-------------------------------------|-----------|----------|
| S1 1 | | | |
| H1 2 | | | |
| M1 1 | 12" X 16" X 3/4" X 4" 300# MANWAY | SA-106-C | |
| F1 3 | 3"-NPT 1500# RADIAL FLANGE | SA-181-70 | |
| F2 1 | 3"-NPT 1500# FLAT FLANGE | SA-181-70 | |
| F3 1 | 2"-NPT 1500# FLAT FLANGE | SA-181-70 | |
| C1 1 | 1 1/2"-NPT 3000# FULL COUPLING | SA-105 | |
| F4 1 | 1 1/4"-NPT 1500# RADIAL FLANGE | SA-181-70 | |
| C2 1 | 3/4"-NPT 3000# FULL COUPLING | SA-105 | |
| F5 2 | 1/2"-NPT 1500# FLAT FLANGE | SA-181-70 | |
| A1 1 | BAFFLE | A84451 | |
| A2 2 | 1/2" X 4" X 4" STANDARD LIFT LUG | SA-516-70 | A84386 |
| S2 4 | 1/2" X 5" X 5" PAD | SA-516-70 | |
| S3 4 | 3/8" X 4" X 4" ANGLE LEG X 29" LONG | SA-36 | |
| NP 1 | ASME DATA PLATE | C1010 | |

| DATE | BY | REVISION | APP | XREF | REV | NOTES | SPECIFICATIONS | SCALE | DRAWING NO. |
|------|----|----------|-----|------|-----|---|--|-------|-------------|
| | | | | | | INTERIOR FINISH NOTE 1. 1/8" RADIUS ALL EDGES. 2. GRIND ALL INTERNAL WELDS SMOOTH. 3. SANDBLAST TO NEAR WHITE FINISH. 4. ALL VOIDS AND GAPS TO BE CAULKED 5. COAT WITH DEVOE 233H EPOXY. | O.D. 42 LGH. 70.75 MAMP 150 PSI @ 250 F QAL 375 SA WT. 980# CU.T. CODE ASME SECT.VIII, DIV.1 PER DATE OF DWG/LAST REV | NONE | 302518 |



VERTICAL EPOXY LINED WATER TANK

ALL OPEN TAPS TO HAVE PLASTIC THREAD PROTECTORS